


Wall sockets




b=height
angle=15°

Power Twist Wall socket IP66/67

	63 Amp		
	3	4	5
Poles	3	4	5
a	213	213	213
b	173	173	173
Connection type: Contact frame with screws			
Wire flexible [mm ²]	6-16		
solid [mm ²]	6-25		
Contact screws [Ncm]	200 Ncm		
Weight [g]	820	869	923

- contact frame with screws
- housing material: PC/ABS
- contacts: brass with lamellar contact CuBe
 - to order with pilot contact please add a „5“ e.g. 1335-6 (see page 10)
 - to order with pilot contact system (PCS) please add a „6“ e.g. 1336-6 (see page 10)
- top, bottom or rear entry
- housing can be rotated by 180°
- incl. threaded bung
- cable-glands see accessories page 51

IP66/67 watertight
IP44 on request




b=height
angle=15°

Power Twist Wall socket IP66/67

	63 Amp		
	3	4	5
Poles	3	4	5
a	306	306	306
b	195	195	195
Connection type: Contact frame with screws			
Wire flexible [mm ²]	6-16		
solid [mm ²]	6-25		
Contact screws [Ncm]	200 Ncm		
Weight [g]	1360	1409	1463

- contact frame with screws
- housing material: PC/ABS
- contacts: brass with lamellar contact CuBe
 - to order with pilot contact please add a „5“ e.g. 13557-6 (see page 10)
 - to order with pilot contact system (PCS) please add a „6“ e.g. 13567-6 (see page 10)
- top, bottom or rear entry
- housing can be rotated by 180°
- incl. threaded bung
- cable-glands see accessories page 51

IP66/67 watertight
IP44 on request



b=height
angle=15°

Power Twist Wall socket IP66/67

	125 Amp		
	3	4	5
Poles	3	4	5
a	322	322	322
b	205	205	205
Connection type: Contact frame with screws			
Wire flexible [mm ²]	16-50		
solid [mm ²]	16-50		
Contact screws [Ncm]	450 Ncm		
Weight [g]	1745	1752	1852

- contact frame with hexag socket screws
- housing material: PC/ABS
- contacts: brass with lamellar contact CuBe
 - to order with pilot contact please add a „5“ e.g. 1455-6 (see page 10)
 - to order with pilot contact system (PCS) please add a „6“ e.g. 1456-6 (see page 10)
- top, bottom or rear entry
- housing can be rotated by 180°
- incl. threaded bung
- cable-glands see accessories page 51

IP66/67 watertight



Advantages:

Housing can be rotated by 180° – the position of the cable entry can be chosen!

110V~
50/60Hz
4h

230V~
50/60Hz
3p=6h
4p+5p=9h


400V~
50/60Hz
3p=9h
4p+5p=6h

500V~
50/60Hz
7h

>50-500V~
100-300Hz
10h


>50-500V~
301-500Hz
2h

Amp.	Poles	pack. unit	Cat.No.	Cat.No.	Cat.No.	Cat.No.	Cat.No.	Cat.No.
Basic unit HxWxD = 170x118x173; 1xM40; 2xM32								
63	3	2	133-4	133-6	133-9	133-7	133-10	133-2
63	4	2	134-4	134-9	134-6	134-7	134-10	134-2
63	5	2	135-4	135-9	135-6	135-7	135-10	135-2




135-6

Basic unit HxWxD = 262x162x195; 1xM40; 2xØ40								
63	3	2	1337-4	1337-6	1337-9	1337-7	1337-10	1337-2
63	4	2	1347-4	1347-9	1347-6	1347-7	1347-10	1347-2
63	5	2	1357-4	1357-9	1357-6	1357-7	1357-10	1357-2



1357-6

Basic unit HxWxD = 262x162x205; 1xØ50; 2xØ40								
125	3	1	143-4	143-6	143-9	143-7	143-10	143-2
Basic unit HxWxD = 262x162x205; 1xM63; 2xØ40								
125	4	1	144-4	144-9	144-6	144-7	144-10	144-2
125	5	1	145-4	145-9	145-6	145-7	145-10	145-2



145-6



Accessories (cable glands) see page 51

