

Y SPLITTERS C-FORM

DESIGNED AND BUILT TO SATISFY THE CUSTOMERS' SPECIFIC NEEDS IN ACCORDANCE WITH THE I.E.C. REGULATIONS



16Amp	POWER BOX
2D1S2P16	
Y-SPLITTER C-FORM 16amp 1pH+N+E 230V	

configuration:
1 C-FORM 16amp 3p 6h 230V IP44 plug (IN)
2 x C-FORM 16amp 3p 6h 230V IP44 connectors (OUT)
Nominal data: Ue=230V 1pH+N+E, fn=50Hz, InA=16amp, IP=44, Max. power 3.500W



16Amp	POWER BOX
2D1S2P16R	
Y-SPLITTER C-FORM 16amp 1pH+N+E 230V	

configuration:
1 C-FORM 16amp 3p 6h 230V IP44 plug (IN)
2 x C-FORM 16amp 3p 6h 230V IP44 connectors (OUT)
Nominal data: Ue=230V 1pH+N+E, fn=50Hz, InA=16amp, IP=44, Max. power 3.500W

Y SPLITTERS C-FORM

DESIGNED AND BUILT TO SATISFY THE CUSTOMERS' SPECIFIC NEEDS IN ACCORDANCE WITH THE I.E.C. REGULATIONS



configuration:

1 C-FORM 32amp 3p 6h 230V IP44 plug (IN)
2 x C-FORM 32amp 3p 6h 230V IP44 connectors (OUT)

Nominal data: Ue=230V 1pH+N+E, fn=50Hz, InA=32amp, IP=44, Max. power 7.000W

32Amp



2D1S2P32

Y-SPLITTER C-FORM 32amp 1pH+N+E 230V



configuration:

1 C-FORM 32amp 3p 6h 230V IP44 plug (IN)
2 x C-FORM 32amp 3p 6h 230V IP44 connectors (OUT)

Nominal data: Ue=230V 1pH+N+E, fn=50Hz, InA=32amp, IP=44, Max. power 7.000W

32Amp



2D1S2P32R

Y-SPLITTER C-FORM 32amp 1pH+N+E 230V



configuration:

1 C-FORM 32amp 3p 6h 230V IP44 plug (IN)
2 x C-FORM 16amp 3p 6h 230V IP44 connectors (OUT)

Nominal data: Ue=230V 1pH+N+E, fn=50Hz, InA=32amp, IP=44, Max. power 7.000W

32Amp



2D1S322P16

Y-SPLITTER C-FORM 32amp 1pH+N+E 230V

NOTES

Version with IP67 waterproof cable plugs / sockets are available on request.
C-FORM Y-Splitters for usage in non-permanent installations and for temporary use.