

TYPICAL CONFIGURATION



WALL MOUNTING SOCKET DS₂



PLUG DS₂



Wall box metal 60°
392A053



Socket-outlet
3924017



Straight elastomer
352A013D45



Inlet
3928017

MAIN FEATURES

Rated current (with wiring according to standard)	250 A	Ambient temperature	-40 °C to +60 °C
Maximum voltage	1000 V	Flexible wiring (min-max)	70 - 95 mm ²
IP protection lid closed	IP55	Stranded wiring (min-max)	70 - 120 mm ²
IP protection connected plug	IP54	Keying positions	12
Shock resistance	IK09		

LOAD-BREAK CAPABILITY OF THE DECONTACTOR™

Comply with IEC EN 60309-1 and IEC EN 60309-4 standards	(250 A / 500 V) or (200 A / 690 V)
Load-break capability according to IEC EN 60947-3 / AC-22A	(250 A / 400 V) or (125 A / 690 V)
Load-break capability according to IEC EN 60947-3 / AC-23A	160 A / 440 V
Short-circuit current I _{cc}	10 kA

DUAL VOLTAGE SOCKET-OUTLET
(SEE P.8)

Voltage 50 Hz	Polarity	Part no.	Part no.
190 - 230 V	3P+E	3924033	3928033
380 - 440 V	3P+E	3924013	3928013
220 - 250 V / 380 - 440 V	3P+N+E	3924017	3928017
660 - 690 V	3P+E	3924193	3928193
380 - 440 V / 660 - 690 V	3P+N+E	3924197	3928197
1000 V	3P+E	3924223	3928223

SOCKET-OUTLET female
DS₂ (250 A)



INLET male
DS₂ (250 A)



► Other voltages, frequencies and contact configurations are available (see page 10).

AUXILIARY CONTACTS

Socket-outlet with 2 auxiliary contacts (5 A / 400 V)	Socket no. + 972
Inlet with 2 auxiliary contacts (5 A / 400 V)	Inlet no. + 972

For more than 2 auxiliary contacts, please contact us.



CERTIFICAT N°
FR 617263A

BOXES

Cable gland not included



Wall box metal + Inclined metal 60°

BOXES

Cable gland included



Wall box 70° SS

Entry		Entry	
M63	392A053	35-46 mm	394A02563M
M75	392A053475	48-65 mm	392A02575M

SLEEVES



Inclined metal 60°

392A027

HANDLES



Straight elastomer



Straight metal



Straight poly without cable gland with metric threaded entry



Straight poly with gland for mechanical retention only (no watertightness)

25-35 mm	352A013D35	40-54 mm	392A913	M63	392A253463	40-63 mm	392A253D63
35-45 mm	352A013D45	54-63 mm	392A913-63	M75	392A253475		
45-49 mm	352A013D49						

INFO +

400 A / 1000 V connecting device

DS4 is a plug and socket-outlet that can work with up to 400 A as a connector without load-breaking capacity. It is available in 2P+E or 3P+E version with 2 pilot contacts for electrical interlocking.

Advantage: The DS4 has the same interface as the DS2 and is just as easy to operate. See HIGHT CURRENT RANGE (page 100).



ACCESSORIES & OPTIONS

**Locking with shaft for 2 padlocks
ø 8 mm (padlocks not supplied)**

Socket no. + 844

Lockable plug: contact us

Padlocking device 1 to 6 padlocks
873A541

Inlet cap
312A126

180° opening lid
Self-returning lid
180° opening and self-returning lid
IP66/IP67 (socket & inlet)

Socket no. + 10
Socket no. + R
Socket no. + 18
Part no. + 600

